

HEXAGON HEAD BOLTS WHITE ZINC GALVANISED (MILD STEEL) GRADE 4.6

A1

สกรูมิลเหลี่ยมขาว (เกรด 4.6)

	STANDARD	JIS B1180
	MATERIAL	SWRCH6R (MILD STEEL)
	COATING	WHITE ZINC
	CODE	ABH, BBH, WFP, BSZ
	UPDATE	01-08-2010

d (Diameter)	M5	M6	M8	M10	M12
p (pitch)	0.8	1.0	1.25	1.25	1.5
k (Head Thickness)	3.5	4.0	5.3	6.4	7.5
s (Width across flat)	8	10	12	14	17
b (Thread Length)	16	18	22	26	30

Length (mm.)	Size					
	M5	M6	M8	M10	M12	
10		1,000	1,000	600		
12		1,000	700	600		
15		1,000	600	500		
20		1,000	500	400	300	
25		1,000	400	300	200	200
30		1,000	300	300	200	100
35		1,000	300	200	200	100
40		300	200	200	200	100
45		500	200	200	200	100
50		600	300	200	200	100
55			400	250	150	100
60			400	200	150	100
65			300	200	150	100
70			300	200	150	100
75			300	200	150	100
80			300	200	100	100
90			300	200	100	50
100			300	150	100	50
110				150	100	
120				100	100	
125		ใต้เส้นคู่=เป็นไซซ์พิเศษ		100	80	
130				100	80	
140				100	80	
150				100	80	

หัวน็อตมิลขาว										
d (Diameter)	M2	M3	M4	M5	M6	M8	M10	M12		
p (pitch)		0.5	0.7	0.8	1.0	1.25	1.25	1.5		
m (Head Thickness)		2.3	3.1	4.5	5.0	6.5	8.0	10.0		
s (Width across flat)		5	7	8	10	12	14	17		
Size	M2	M3	M4	M5	M6	M8	M10	M12		
หัวน็อตขาว Hex Nut w zinc	15,000		5,000		2,000		2,000		1,000	500
อีแปะขาว Plain Washer w/z			5,000		3,000		2,000		2,000	1,000
สปริงขาว Spring Washer w/z			30,000		15,000		8,000		4,000	2,500
									1.25 x 12	1.25 x 14
										1.5 x 17

