

HEXAGON SOCKET HEAD CAP SCREWS GRADE 12.9

A25

สกรูหัวจมดำ เกลียวทึน BSW (เกรด 12.9)

	STANDARD	ANSI B18.3
	MATERIAL	12.9
	COATING	BLACK
	CODE	ASC
	UPDATE	31-05-2010

d (Diameter)	3/16	1/4	5/16	3/8	7/16	1/2W	1/2C	5/8	3/4	7/8	1"	1.1/4	1.1/2
p (pitch)	24	20	18	16	14	12	13	11	10	9	8	7	6
dk	7.9	9.5	11.7	14.2	16.5	19	19	23.6	28.3	33	38	47	57
k (Head Thickness)	3/16	1/4	5/16	3/8	7/16	1/2	1/2	5/8	3/4	7/8	1"	1.1/4	1.1/2
s (Hex Key)	5/32	3/16	1/4	5/16	5/16	3/8	3/8	1/2	5/8	3/4	3/4	7/8	1"
b		25.4	28.45	31.75	35.05	38.1	38.1	44.45	50.8				

Length (inch)	Size												
	3/16 (#10)	1/4	5/16	3/8	7/16	1/2 12G BSW	1/2 13G NC	5/8	3/4	7/8	1"	1.1/4	1.1/2
3/8	200	200											
1/2	200	200	100							ในกรอบ			
5/8	200	200	100	100						บนเส้นคู่=เกลียวตลอด (FULL THREAD)			
3/4	200	200	100	100									
1"	200	200	100	100	100	100	100	50					
1.1/4	200	200	100	100	100	100	100	50					
1.1/2	200	200	100	100	100	100	100	50	25				
1.3/4	200	200	100	100	50	50	100	50	25				
2"	200	200	100	100	50	50	100	25	25	15	15		
2.1/2		200	100	100	50	50	100	25	20	15	15		
3"		200	100	100	50	50	100	25	15	15	15	10	10
3.1/2		200	100	50	50	50	50	25	15	12	15	10	10
4"		200	100	50	50	50	50	25	15	12	10	10	10
4.1/2			100	50	50	25	25	25	15	12	10	10	5
5"			100	50	50	25	25	25	15	12	10	10	5
6"			100	50	50	25	25	25	15	12	10	10	5
7"						25	25	25	15	10	10	5	5
8"		นอกกรอบ ถอย 10%					25	25	15	10	10	5	5
9"	ใต้เส้นคู่=เกลียวครึ่ง (PARTIAL THREAD)						25	25	15	10	10	5	5
10"						25		25	15	10	10	5	5
11"								25	15	10	10	5	5
12"									25	15	10	10	5

บริเวณใต้เส้นคู่ (=) ลงมาเป็นเกลียวครึ่ง

บริเวณใต้เส้นทึบ (-) ลงมานอกกรอบเป็นไซซ์พิเศษ ส่วนลดถอย 10%

